



### Technische Gegevens LAMPE Ballonafsluiter met dubbelconus

Art. nr.	Ballonafsluiter type en uitvoering	Lengte leeg	Lengte gevuld	Gewicht KG	Gebruik in buizen	
		mm	mm		van / mm	tot / mm
<b>76326</b>	<b>Type 1-400</b>	<b>980</b>	<b>960</b>	<b>1,90</b>	<b>100</b>	<b>400</b>
76327	Type 1-400 met speciale dichting	980	960	1,93	150	400
76328	Type 1-400 met bypass (D)	1030	1010	3,55	100	400
76329	Type 1-400 met bypass (D) en speciale dichting	1030	1010	3,60	150	400
<b>76336</b>	<b>Type 1-600</b>	<b>1240</b>	<b>1200</b>	<b>3,90</b>	<b>200</b>	<b>600</b>
76337	Type 1-600 met speciale dichting	1240	1200	4,10	250	600
76338	Type 1-600 met bypass (B)	1360	1320	11,80	200	600
76339	Type 1-600 met bypass (B) en speciale dichting	1360	1320	12,00	250	600
<b>76341</b>	<b>Type 1-800</b>	<b>1720</b>	<b>1670</b>	<b>8,60</b>	<b>300</b>	<b>800</b>
76342	Type 1-800 met speciale dichting	1720	1670	9,50	300	800
76343	Type 1-800 met bypass (B)	1840	1790	18,80	300	800
76344	Type 1-800 met bypass (B) en speciale dichting	1840	1790	19,50	300	800
<b>76346</b>	<b>Type 1-1000</b>	<b>2080</b>	<b>2040</b>	<b>11,80</b>	<b>400</b>	<b>1000</b>
76347	Type 1-1000 met speciale dichting	2080	2040	12,40	400	1000
76348	Type 1-1000 met bypass (B)	2190	2250	23,70	400	1000
76349	Type 1-1000 met bypass (B) en speciale dichting	2190	2250	24,00	400	1000
<b>76356</b>	<b>Type 1-1400</b>	<b>2880</b>	<b>2760</b>	<b>25,20</b>	<b>500</b>	<b>1400</b>
76357	Type 1-1400 met speciale dichting	2880	2760	27,90	500	1400
76358	Type 1-1400 met bypass (B)	3010	2940	41,50	500	1400
76359	Type 1-1400 met bypass (B) en speciale dichting	3010	2940	44,20	500	1400
<b>76361</b>	<b>Type 1-1600</b>	<b>3170</b>	<b>3110</b>	<b>38,50</b>	<b>600</b>	<b>1600</b>
76362	Type 1-1600 met speciale dichting	3170	3110	41,80	600	1600
76364	Type 1-1600 met bypass (B) en speciale dichting	3290	3230	58,50	600	1600
<b>76376</b>	<b>Type 1-2200</b>	<b>4360</b>	<b>4380</b>	<b>86,00</b>	<b>1000</b>	<b>2200</b>
76377	Type 1-2200 met speciale dichting	4360	4380	90,40	1000	2200
76379	Type 1-2200 met bypass (B) en speciale dichting	4530	4550	109,40	1000	2200

